

VENTILATED WIRE SHELVING – WEIGHT CAPACITY SPECIFICATION INFORMATION –



FIXED MOUNT Shelving Installation

Weights are safe weight loads. Weight loads are based on ClosetMaid® installation instructions and usage of ClosetMaid® hardware installed in 1/2 in. or 5/8 in. drywall.

Shelving Type	Weight Capacity
12 in. & 16 in. Shelf & Rod	35 lbs /ft.
12 in. & 16 in. SuperSlide®	35 lbs /ft.
16 in. Close Mesh & Linen	35 lbs /ft.
20 in. Close Mesh & Linen	25 lbs /ft.

SHELFTRACK® Shelving Installation

Hang track installation

Drywall - for 1/2 in. and 5/8 in. drywall, drill holes and secure with toggle bolts

Stud Mount - Secure to wall with #12 x 2 in. pan head screw.

Concrete - Drill 1/4 in. holes, insert #12 anchors and secure with #12 x 2 in. pan head screw.

Shelving Type	Weight Capacity
12 in. & 16 in. SuperSlide®	50 lbs /ft. (standard spacing 24 in. max)
Heavy Duty Shelving	100 lbs /ft. (standard spacing 16 in. max)



Architects and Designers: We have details, drawings and specifications available at www.designtools.closetmaidpro.com.