


ADJUSTABLE WIRE SHELVING SYSTEM SPECIFICATIONS & INSTALLATION DETAILS

MOUNTING SYSTEMS

Adjustable ShelfTrack™ Hardware System



A Hang Track

B Standard

C Bracket

D Shelving



Hang Track
Use to hang standards.
Creates one step leveling
and eliminates the need
to install each standard
separately which reduces
installation time. Available
in 40 in. and 80 in. lengths.



Toggle Bolts
Use for drywall
installations.




Screws & Anchors
Use for concrete and
masonry installations.




Standard
Attaches to hang track.
Provides adjustable
height options for
hanging shelving. Space
standards no more than
24 in. apart and no more
than 4 in. from each end
of shelf. Available in 12 in.,
30 in., 48 in., 60 in. and
84 in. lengths.




Bracket
Attaches to standard to
support shelving. Use a
bracket that is the same
depth as your shelving.
Available in 12 in., 16 in.
and 20 in. lengths.
(Exception: 16 in. Shelf &
Rod installation requires
a 12 in. bracket.)



Shoe Shelf Support
Attaches to standard to
support shelf at an angle
for shoes. Shelf should be
installed lip up to keep
shoes in place.



Small End Caps
Large End Caps
Use on cut ends of
shelving to protect
shelving to protect
clothing. Available in
large (Shelf & Rod) and
small (SuperSlide, Close
Mesh, and Shelf & Rod)
shelving sizes.



S&R Shelf End Cap
Use on cut ends of Shelf
& Rod shelving to
protect clothing.




TotalSlide® Shelf Stop
Use on cut ends of
TotalSlide shelving to
protect clothing.


Optional Hardware



Corner Support
For corner installations.
Supports front lip of
shelving to keep it level
where it meets another
shelf in the corner.



**0.5 in. Square Aluminum
or Steel Pole 71 in. & 85 in.**
Use in place of support
brackets when stacking
two or more shelves. Steel
poles are pre-drilled.



Pole Clip & End Caps
Attaches to pole to
support shelving in a
center stack. Pole 11700
and 11800 use self-
drilling screws.
S&R Version: 97700
Linen/SuperSlide Version:
97800
TotalSlide Version: 95200
End Caps: 24700



Universal Shelf Support
Attaches to the back of
shelving to support shelf
at an angle for shoes. Shelf
should be installed lip up
using wall clips to keep
shoes in place.



Universal Joiner Plate
Use to join two shelves
together to create
a continuous run of
shelving. Does not work
for Close Mesh

Shelving Types



SuperSlide®/Linen

The top-of-the-line, continuous-slide closet solution. Available in 12 in. and 16 in. depths. Use in conjunction with SuperSlide hardware. Use as linen shelf without rod.



TotalSlide®

Our quickest and easiest to install, one-piece, continuous-slide closet solution. Available in 12 in. and 16 in. depths.



Shelf & Rod

The economical closet solution. Available in 10 in., 12 in., and 16 in. depths with your choice of a 10 in. or 12 in. hang bar location as measured from the back wall.



Close Mesh


Works best with ShelfTrack for storing small pantry items. Deck wires are 0.63 in. on center vs. 1 in. on center on all other shelving. Available in 6 in., 9 in., 12 in., 16 in. and 20 in. depths.



Linen


The perfect answer to every basic shelving need in every room. Available in depths of 6 in., 9 in., 20 in. and 12 in. double lip.

SuperSlide® Hardware




Closet Rod Support

Attaches to SuperSlide shelving to support closet rod. Use one every 36 in. at each end.



0.75 in. Closet Rod

Snaps into closet rod support to allow hangers to slide without interruption.



Internal Closet Rod Cap

Use on ends of closet rods to keep hangers on rod.



Corner Closet Rod

Use with SuperSlide shelving to create uninterrupted sliding action around corners. Support with closet rod supports.

Installation and Materials Specifications

HangTrack, Standards and Brackets:

Horizontal track mount, level track, secure with screws and/or mollys in studs or drywall. Horizontal track can also be mounted to the top wall/ceiling plate with #12 x 2 in. pan head screw #287600. Secure to at least one stud. Vertical installation of standards no more than 24 in. apart on studs. Attach shelf brackets which can be used with SuperSlide, Heavy Duty, Linen, Shelf & Rod and Close Mesh 12 in., 16 in., or 20 in. Decking.

End brackets to support the front of the shelves:

Install on the same level line as the wall clips and center on the front rods of the shelves. All shelves must be front supported a maximum of every 36 in. with an end bracket, support bracket or pole. End brackets #94000, #94100, #94200 (for SuperSlide®), #93200, #93300 (other shelves).

Drywall:

Drill 0.25 in. hole, insert #91000 or #91100 wall clip. Use #8 pin to expand anchor.

Wood:

Drill 0.25 in. hole into wood. Secure wall clip with #8 1 in. screw, or secure pole clip #97800 directly to wood with #8 1.25 in. screw #22800.

Concrete:

Drill 0.25 in. hole with masonry bit. Insert wall clip #91000, secure with #8 1 in. screw #20800.

Pole:

Use pole clip #97800 for linen shelving and clip #97700 for Shelf & Rod shelving on pole #21700 or #211800. Pole #211800 recommended for SuperSlide installation.

Corner Support Brackets:

Use on all corner "butt" joints #12000.

Cutting Shelves:

Shelves are to be cut 0.5 in. to a maximum of 1.38 in. shorter than the actual wall measurements or the desired shelf length.

All exposed cut ends are to be capped with #20300 or #20400 depending on the shelf.

SuperSlide Component Installation:

Place hang bar supports #92500 or #567200 every 24 in. to 36 in. (place support bracket #116400 adjacent to support) use SuperSlide end bracket #97900 or #98000 at side wall where pole is used. Use 12 in. support brackets for 12 in. or 16 in. depth shelves. Place pole caps #208300 or #208100 on cut end of pole. Use pole connector #208500 to connect two pieces of 0.75 in. hang bar #201200 (white) or #207100 (chrome). When using pole connector, joint must rest in #92500 or #567200 bracket. For wall installation, use end bracket #97900 or #98000. Down clips #97800, #98100 or #61200 must be used on all open end installations.

TotalSlide Component Installation:

Use side wall bracket #94700 or #94800; pole clip #95200 or #95100; and shelf stop #96900.

General Specifications:

Furnish and install ClosetMaid Vinyl-Coated, Steel-Rod, Ventilated Shelving and Storage Systems manufactured by ClosetMaid Corp., Ocala, Florida, in all closets.

Wire Shelving Physical Properties:

Materials	Grade c-1006 basic cold drawn steel wire
Tensile strength	Over 100,000 PSI (average)
Cross deck spacing	0.63 in. to 1 in. increments
Coating	Proprietary polyvinyl chloride formula resin (PVC)
Vinyl thickness	9-11 mills (fluidized bed process)
Mounting hardware	Components shall provide for shelving installation to drywall without requiring mounting to concealed wall structural members. Support brackets shall be required for 36 in. span. (24 in. recommended for areas designed for heavy use.)

Coating Specifications:

ClosetMaid heavy duty vinyl coating won't chip or split. It is a proprietary Polyvinyl Chloride Resin (PVC) with an exclusive mixture of ingredients including plasticizers, stabilizers, pigments and other additives—none of which are listed as hazardous materials on OSHA 29CFR1910.1017.

ClosetMaid's patented plastic components are manufactured to get high performance standards and meet rigid material requirements. Nylon is specified for toughness. Hi-impact styrene is specified for rigid strength. Polypropylene is specified for consistent performance. Manufacturer reserves the right to change specifications without notice.

For more information visit www.closetmaidpro.com



13485 Veteran's Way Suite 200
Orlando, FL 32827 Toll - Free #
1-800-221-0641
www.closetmaid.com
© 2019 ClosetMaid LLC
06-11514-00 (05/19)

If a professionally installed ClosetMaid® product does not give the user complete satisfaction when installed in accordance with the manufacturer's instructions, and by an Authorized ClosetMaid Dealer, it will be exchanged free of charge. Please note that only the unsatisfactory part in a multi-piece product will be exchanged.

