




Induction Welded Membrane - Cover Board - Insulation - Existing Roof - Lightweight Concrete Deck (Recover)



| Fire Rating / Max. Slope | Deck Type | Cover Board/Insulation (over Existing Roof) | | | IB Membrane Attachment | Max. Design Pressure** |
|-----------------------------|----------------------------|---|--|--|--|--------------------------------|
| | | Type | Fastener | Attachment | | |
| 'Class "A" Unlimited | Lightweight Concrete/Steel | Approved Cover Board & Approved Insulation | Min. IB HD #14, 3" IB isoweld Plate | 2x3-ft grid, staggered (6 per 4' x 8') | Plate bonded with isoweld 3000 tool | Minimum Req for IB Warranty |
| 'Class "A" Unlimited | Lightweight Concrete/Steel | Approved Cover Board & Approved Insulation | Min. IB HD #14, 3" IB RhinoBond Plate | 2x3-ft grid, staggered (6 per 4' x 8') | Plate bonded with RhinoBond tool | Minimum Req for IB Warranty |

Existing Roof: APP or SBS modified bitumen, smooth or granule surfaced asphaltic built-up roof, or single-ply membrane (CPA, CSPE, EPDM, PVC, or TPO)

Approved Insulation: IB EnergyBoard II or III, or IB Approved UL Classified Polyisocyanurate, IB Approved UL Classified Expanded Polystyrene, IB Approved UL Classified Extruded Polystyrene Insulation

Approved Cover Board: DensDeck, DensDeck Prime, DensDeck StormX, Securock Ultralight Glass-Mat, Securock Ultralight Coated Glass-Mat, Securock Gypsum Fiber Board, DexCell Glass-Mat Roof Board, or DexCell FA Glass Mat Roof Board, minimum 1/2" thickness; or minimum 1/2" thickness IB HD ISO or H-Shield HD ISO, or minimum 1/2" thickness StructoDeck HD Primed.

Fire Classification Note: ¹Maintains existing classification with unlimited slope but is limited to existing Class A to retain existing Class 'A' Classification, over insulated or uninsulated cap sheet or smooth surfaced roof when covered with minimum 1/2-in. thickness UL Classified gypsum cover board. ²UL Class A up to 1":12" slope over insulated or non-insulated cap sheet, smooth or gravel surfaced BUR (gravel may be removed) or PVC roof system, covered with minimum 1/4-in. thick DensDeck, DensDeck Prime, Securock Glass-Mat Roof Board, DexCell Glass Mat Roof Board, or DexCell FA Glass Mat Roof Board, or minimum 7/16-in. thick DexCell Cement Board. ³Maintains existing classification limited to 1/2":12" slope and limited to any existing Class A, B, or C roofing system to retain existing Classification, when covered with 1/2-in. thick IB HD ISO or H-Shield HD ISO. ⁴Recover over modified bitumen, or over Single-Ply may not retain UL Classification. ⁵Use of other IB Approved cover boards or lesser thicknesses may not retain UL Classification.

**Refer to Substrate Resistance Table for required pull-out values.

For additional information about IB Roof Systems requirements, recommendations, installation details, approvals, and limitations for the above assemblies, please refer to the latest edition of the IB Roof Systems Specifications Manual. For Technical Services please contact IB Technical Department at 800-426-1626.

| Membranes: | Membrane Color: | | | | | Warranty Length*** | | | Warranty Type*** |
|--------------------------|-----------------|------------|-------------|--------|------------|--------------------|---------|---------|--|
| IB PVC Single-Ply 50 Mil | White* | Gray | Tan | Bronze | ChemGuard* | 10 Year | 15 Year | 20 Year | Total Systems - No Dollar Limit (TSW) |
| IB PVC Single-Ply 60 Mil | White* | Cool Sand* | Cool Stone* | Gray | Tan | 15 Year | 20 Year | 25 Year | Warranty Plus (WP) |
| IB PVC Single-Ply 80 Mil | White* | Gray | Tan | Bronze | ChemGuard* | 15 Year | 20 Year | 25 Year | Commercial Limited Material Warranty (CLMW) |
| | | | | | | | | | Residential Limited Material Warranty (RLMW) |

*Meets CRRC, Title 24 & EnergyStar Standards

***Refer to Warranty Selection Guide for Warranty Riders, Term Length Limitations, and eligibility requirements of the Warranty Program

Submitted By:

Address:

Email:

Project Name:

Address:

